

LogoMatic G2

Logotherm® decentralised interface stations







Now that's smart

With **Logotherm®** interface stations, several primary energy sources (e.g. renewable energy systems such as solar integration) can be connected for optimal network operation and is also conveniently controlled via app.

- Control of domestic hot water circulation times and temperatures
- Communication of service intervals & operating hours data
- Commissioning assistant
- Pasteurisation (Disinfection) mode possible when using domestic hot water secondary circulation
- Adjustable hot water temperatures



Feel-good factors for a climate control

- Available in 3 different domestic hot water output classes
- Precise hot water preparation even with varying primary (Network) temperatures
- State-of-the-art control for heating or cooling demand*
- High level of energy efficiency, having positive effect on the energy balance of your network. This is due to the integrated design, control innovations, choice of components (e.g. HE pump) as well as EPP full insulation and low return temperatures
- Attractive visual design, incoproating an insulating housing (surface-mounted) or as a flush-mounted version (from 110 mm installation depth) for "invisible" and discreet integration in the living space



The effect of Logomatic G2 with insulation housing



Calculated energy saving potential of 10%



Reduced life cycle costs when compared to other interface stations



Additional comfort control for the consumer

United Kingdom Flamco Limited +44 17 447 447 44 info@flamco.co.uk The Netherlands
Flamco Group
+31 33 299 75 00
info@flamcogroup.com

www.flamcogroup.com

 $^{^{\}star}$ Depending on the type of station. For more information, please contact your Flamco representative.